



We Know Water.

INTRODUCING MAXXFILL™ PULSE

Touch-Free. Bottle-Free.

MaxxFill Pulse is aligned with what's most important to customers today -- the safety of touch-free filling, combined with easy access to unlimited, on-demand water.

All MaxxFill™ products include advanced features to meet the changing hydration needs of users.



*Measured at 70psi water pressure.



wavesense filling

Activate filling with a wave of your hand, limiting the spread of germs and pathogens.



everstream™ system

*Fill up faster with 29% higher flow rate (2.7 LPM) than standard bottle coolers.**



bottle flex™ alcove

Tallest on the market (13"); fits virtually any size bottle without tipping.

Why MAXXFILL Pulse:

- Fill your bottle with a wave of your hand with our WavSense™ Technology
- Plumb directly to water line in combination with your preferred filtration system for an endless supply of great tasting water
- LED night light in front alcove
- Convenient hot, cold, and room temperature water dispensing

Cold Water Refrigeration Unit:

Convection cooled condenser. Internal, spring mounted, hermetically sealed compressor with automatic overload protector requires no lubrication. Refrigerant is controlled by a capillary tube.

Cold Water Reservoir:

Type 300 series stainless steel with external aluminum evaporator plate. Encased in pre-fitted molded plastic foam insulation. Adjustable mechanical cold control.

Two-Piece Hot Water Tank:

500 watt easy to service or replace heating element. Tank is easy to replace or service without breaking soldered refrigeration connections. Hot tank is a type 300 series stainless steel.

Hot Water Capacity:

45 x 6 oz. cups of piping hot water per hour. 1-1/2 quart storage tank.

Hot Water Safety Activation:

Hot water activation requires a two-step action that is easy for adults to use but protects small children.

Drip Receptor:

Durable dishwasher safe drip tray lifts out for easy cleaning.

Electrical:

115 volts, 60 hertz, 1/20 hp water cooler compressor. Three wire service cord & polarized plug.



Choose from a range of filter options to maximize taste. Quick and easy installation and replacement with access door.

p1cmprhsk				
	depth	width	height	weight
PRODUCT	14.2"	12.2"	42.33"	33 lbs
PACKAGING	15.7"	14"	45.7"	38 lbs
cold water capacity/dimensions	room temp	water temp	gallons per hour at 50°F	number of 3 oz. cups per hour
	70°F	80°F	2	85
	80°F	80°F	1.5	64
	90°F	80°F	0.9	38
	100°F	80°F	0.6	25



WARNING:
Cancer and Reproductive Harm
www.P65Warnings.ca.gov

Specifications are subject to change without notice.



Making Your Workplace More Productive

Toll Free: (800) 858-1180 | Email: customerservice@warehousedirect.com

Address: 2001 S Mount Prospect Rd Des Plaines, IL 60018 | Phone: (847) 631-3470