

WRL-4000 Series- 40" Roll Laminator

WRL-4000-HR • WRL-4000-Plus
WRL-4000-Pro • WRL-4000-Pro Dual



The WRL-4000 Series is a MADE-IN-THE-USA easy-to-operate 40" heated roller roll laminator specifically engineered to meet the laminating needs of schools, businesses, and other organizations searching for an economical and versatile laminating solution. The WRL Series is designed to meet the needs and budgets of all potential users. The basic functionality and mechanics are the same for all versions, with additional features added to each incremental model. The series comes standard with an Auto Shut Off feature designed to protect the rollers from overheating and excess wear. We offer fixed or variable speed versions, we also offer machines with or without horizontal end trimmers. The WRL Series, depending on the model selected, is capable of laminating films from 1.5 to 10 mil in thickness & has 3/16" mounting capability. Call to discuss your options today!

KEY FEATURES:

- Heated Roller Laminator
- Adjustable Temperature Control
- Adjustable Speed Control
- Mounting Capable w/o Nip Control
- 2" or 2.5" Diameter Silicone Heated Rollers
- Safety Shield
- Electric Heat Control w/LED Readout
- Reverse Function
- Auto Shutoff
- 110 Volt Machine
- 1 Year Warranty
- Made-in-the-USA



WRL-4000 Series- 40" Roll Laminator


WRL-4000-HR • WRL-4000-Plus

WRL-4000-Pro • WRL-4000-Pro Dual

Specifications:

	WRL-4000-HR	WRL-4000-Plus	WRL-4000-Pro	WRL-4000-Pro Dual
				
Features				
Width	40"	40"	40"	40"
Housing	Elite or Budget	Elite	Elite	Elite
Film Gauge	1.5 & 5 MIL	1.5 & 5 MIL	1.5 - 10 mil	1.5 - 10 mil
Speed Range	0-9 ft/ min	0-9 ft/ min	0-10 ft/ min	0-10 ft/ min
Heating Method	Heated Roller	Heated Roller	Heated Roller	Heated Roller
Cold Lamination (PSA Rewind)	No	No	No	No
Speed Control	Variable	Variable	Variable	Variable
Temperature Control	Variable	Variable	Variable	Variable
Temperature Controllers	Single	Single	Single	Dual
Ready Light	Yes	Yes	Yes	Yes
Auto Shutoff	No	Yes	Yes (Selectable)	Yes (Selectable)
Reverse Function	Yes	Yes	Yes	Yes
Mounting Capability	3/16"	3/16"	3/16"	3/16"
Roller Gap Adjustment	Self Adjusting	Self Adjusting	Self Adjusting	Self Adjusting
Core Size/Core Adapter	1"	1" (3" Optional)	1" & 3"	1" & 3"
Display Type	LED	LED	LED	LED
Safety Shield	Yes	Yes	Yes	Yes
Safety Shield Safety Switch	No	No	No	No
Key Pad Control	Yes	Yes	Yes	Yes
Warm Up Time	12 Minutes	12 Minutes	12 Minutes	12 Minutes
Slide Away Lower Roller Ideal Bar Release Mechanism For Easy Film Loading	No	No	No	No
Cooling Fans	No	No	Yes	Yes
Built-in Horizontal Trimmer	No	Yes	Yes	Yes
Heat Roller Diameter	2"	2"	2.5"	2.5"
Heater Type	Incoloy	Incoloy	Incoloy	Incoloy
Power	120 Volt/60 Htz	120 Volt/60 Htz	120 Volt/60 Htz	120 Volt/60 Htz
Wattage/Amps	1400 Watts/12 Amps	1400 Watts/12 Amps	1400 Watts/12 Amps	1400 Watts/12 Amps
Dimensions	48.5" x 18.5" x 11.38"	48.5" x 18.5" x 11.38"	48.5" x 18.5" x 11.38"	48.5" x 18.5" x 11.38"
Weight/Ship Weight	93 Lbs/136 Lbs	93 Lbs/136 Lbs	93 Lbs/136 Lbs	103 Lbs/146 Lbs
Ships Via	LTL	LTL	LTL	LTL
Country of Origin	USA	USA	USA	USA
Diameter of Feet (For Cabinets)	40 3/4"	40 3/4"	40 3/4"	40 3/4"
Warranty	1 Year	1 Year	1 Year	1 Year
Feed Table	Painted Feed Tray	Painted Feed Tray	Painted Feed Tray	Painted Feed Tray
Feed Table Alignment Guide	No	No	No	No
Feed Table Safety Switch	No	No	No	No
Mandrel Type	Hex Shaft	Hex Shaft	Hex Shaft	Hex Shaft
Key Lock	Optional	Optional	Optional	Optional

Control Panels



Applications:

- | | |
|--------------|----------------|
| Posters | Banners |
| Displays | Maps |
| Photos | Charts |
| Game Boards | Signs |
| Bookmarks | Visual Aids |
| Menus | Labels |
| Certificates | Teaching Aids |
| Awards | Digital Prints |